

## Emerald® Product Comparison

Feature	Emerald 4K	Emerald DESKVUE	Emerald PE	Emerald SE	Emerald ZeroU TX	Emerald Remote App
Max Video Resolution	4096 x 2160 at 60 Hz  (DisplayPort 1.2)  Single Monitor	5120 x 1440 at 60 Hz  (DP 1.2/HDMI 2.0)  Quad Monitor	1920 x 1200 at 60 Hz (DVI [TX and RX], DisplayPort [TX only])  SE/PE: Single or Dual Monitor			1920 x 1200 at 60 Hz
Video Quality	Pixel Perfect			Visually lossless		High quality ~35 fps
Dual Network Ports	Yes, (2) SFP+	Yes, (2) CATx	Yes, (1) SFP, (1) CATx	No, (1) CATx		-
Peripheral Support	All USB 2.0 devices	USB 3.2, USB 2.0	All USB 2.0 devices		USB HID only	
VM Support	PCoIP*, RDP/RemoteFX  * Supports PCoIP with EMD3000GE.	PCoIP*, RDP/RemoteFX  * Supports PCoIP with EMD3000GE.	RDP/RemoteFX	RDP/Remote FX	-	RDP/RemoteFX
Bidirectional Analog Stereo Audio	•	•	•	•	(Speaker only)	(Speaker only)
System Scalability	Point-to-point extension up to unlimited KVM matrix					

MORE INFORMATION  [BLACKBOX.COM/EMERALD](https://blackbox.com/emerald)